

NETXS

Cat6A U/FTP Cable




Application:

- Horizontal Cabling, Backbone Cabling, Digital and Analog Audio and Video Signal Transfer
- IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T, 10Gbase-T
- IEEE 802.5 16 MB; ISDN; TPDDI; ATM
- Power over Ethernet (PoE / PoE+) / Type 1-4

Standards:

- ANSI / TIA-568.2-D & ISO / IEC 11801
- EN 50173-1; EN 50288-10-1
- IEC 61156-5
- IEEE 802.3 af / at / bt



Flame Resistance:

LSHF: EN 60332-1; EN 60754-1 & 2, EN 61034-2, Class CPR-Eca / Dca / Cca
 PVC: EN 60332-1 Class CPR-Eca

Construction:

Conductor	ETP-grade copper Ø 23 AWG
Insulation	Foamed Polyethylene
Twisting	2 insulated conductors forming one pair
Cable Lay-up	4 twisted pairs
Shield	Individual pair shielded with aluminum polyester tape, tinned copper drain wire
Sheath	LSHF / PVC
Nominal Cable Diameter	7.5 mm

Mechanical Properties:

Bending Radius : Min 8 x Cable Diameter at -20°C ± 1°C
 Pulling Force : 112 N

Temperature Range

Installation : 0° to +50°C
 Operation : -20° to +70°C

Electrical Properties at 20°C:

Characteristic Impedance	: 100 + 15 Ω	Resistance Unbalance	: 5% Max
Conductor Resistance	: < 9.38 Ω / 100m	Capacitance Unbalance	: 330pF / 100m
Mutual Capacitance	: < 5.6nF / 100m	Delay Skew	: < 45Ns

Transmission Characteristics at 20°C:

Frequency (MHz)	Max. Attenuation (dB/100M)	RL (dB) Min.	NEXT (dB) Min	PSNEXT (dB) Min.	ACRF (dB) Min.	PSACRF (dB) Min.
1	2.1	20.0	74.3	72.3	67.8	64.8
4	3.8	23.0	65.3	63.3	55.8	52.8
10	5.9	25.0	59.3	57.3	47.8	44.8
16	7.5	25.0	56.2	54.2	43.7	40.7
20	8.4	25.0	54.8	52.8	41.8	38.8
31.25	10.5	23.6	51.9	49.9	37.9	34.9
62.5	15	21.5	47.4	45.4	31.9	28.9
100	19.1	20.1	44.3	42.3	27.8	24.8
200	27.6	18.0	39.8	37.8	21.8	18.8
250	31.1	17.3	38.3	36.3	19.8	16.8
300	34.3	16.8	38.1	35.1	18.3	15.3
500	45.3	15.2	33.8	31.8	13.8	10.8

Color Code:

PAIR NO	COLOR
1	White and Blue
2	White and Orange
3	White and Green
4	White and Brown

Jacket Color (C1 C2):

 Grey (01)	 Blue (02)
 Red (03)	 White (04)
 Violet (05)	 Orange (06)
 Yellow (07)	

Packaging: Available in Reelex II Packing of 305m (1000ft) **(03)**
 Available in Reel of 305m(1000ft) **(04)** / Reel of 500 m(1640ft) **(05)**
 Length Tolerance: +/- 2 meter

Product Code / Part No:

Part No	Product Name	Euro Class
32527-C1C2P1P2	Cat 6A U/FTP-LSHF	CPR-Eca
32528-C1C2P1P2	Cat 6A U/FTP-LSHF	CPR-Dca
32529-C1C2P1P2	Cat 6A U/FTP-LSHF	CPR-Cca
31527-C1C2P1P2	Cat 6A U/FTP-PVC	CPR-Eca

Refer to Jacket Color and Packaging details for C1C2 and P1P2 respectively



The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, Sterlite Technologies makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. Sterlite Technologies obligations shall be only set forth in Sterlite Technologies standard terms and conditions of the sale and in no case, Sterlite Technologies be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product.

Users of Sterlite Technologies products should make their own evaluation to determine the suitability of such each product for the specific application.