



Fiber Cable Assemblies

STL Fiber Optic Cable Assemblies are designed for use in telecommunications, CATV, data communications and wide area network applications. Pigtails are single fiber cables preassembled with a connector at one end. They are typically used to terminate primary coated fiber to optical equipment. Patch cords / Jumpers are single fiber cables preassembled with a connector(s) at both ends to cross-connect patch panel to patch panel and to interconnect patch panels to optical equipment. For all connectors used on the pigtails and patch cords / jumpers, the matching connector mating adapter kits are available and can be ordered separately.



SPECIFICATIONS

Type of Conn.	Insertion Loss (Typical)	Return Loss (Min.)	Connector Body Color	Boot Color
SC/PC	0.30dB	20dB	Beige	Blue / White
LC/PC	0.30dB	20dB	Beige	White

Fiber Type	OM4	End face Criteria	IEC 61300-3-35
Cable Diameter	2mm/0.9mm	IL Measurement	IEC 61300-3-4
Jacket Color	Aqua	BR measurement	IEC 61300-3-6

The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, Sterlite Technologies makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. Sterlite Technologies obligations shall be only set forth in Sterlite Technologies standard terms and conditions of the sale and in no case, Sterlite Technologies be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product. Users of Sterlite Technologies products should make their own evaluation to determine the suitability of such each product for the specific application.