

estelan

Cat6A F/FTP Cable




Application:

- Horizontal Cabling, Backbone Cabling, Digital and Analog Audio and Video Signal Transfer
- IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T, 10Gbase-T
- IEEE 802.5 16 MB; ISDN; TPDDI; ATM
- Power over Ethernet (PoE / PoE+) / Type 1-4

Standards:

- ANSI / TIA-568.2-D & ISO / IEC 11801
- EN 50173-1; EN 50288-10-1
- IEC 61156-5
- IEEE 802.3 af / at / bt



Flame Resistance:

LSZH: EN 60332-1; EN 60754-1, Class CPR-Eca & CPR-Dca

Construction:

Conductor	ETP-grade copper Ø 23 AWG
Insulation	Foamed polyethylene
Twisting	2 insulated conductors forming one pair
Cable Lay- up	4 twisted pairs
Shield	Individual pairs / overall core shielded with aluminium / polyester tape, drain wire
Sheath	LSZH
Nominal Cable Diameter	7.5 mm

Mechanical Properties:

Bending Radius : 8 x Cable Diameter at -20°C ± 1°C
 Pulling Force : 112 N

Temperature Range

Installation : 0° to +50°C
 Operation : -20° to +70°C

Electrical Properties at 20°C:

Characteristic Impedance : 100 + 15 Ω
 Conductor Resistance : < 9.38 Ω / 100m
 Mutual Capacitance : < 5.6nF / 100m

Resistance Unbalance : 5% Max
 Capacitance Unbalance : 330pF / 100m
 Delay Skew : < 45Ns

Transmission Characteristics at 20°C:

Frequency (MHz)	IL (dB) Max.	RL (dB) Min.	NEXT (dB) Min.	PSNEXT (dB) Min.	ACRF (dB) Min	PSACRF (dB) Min	Prop.Delay (ns) Max.
1	2.1	20.0	74.3	72.3	67.8	64.8	570
4	3.8	23.0	65.3	63.3	55.8	52.8	552
10	5.9	25.0	59.3	57.3	47.8	44.8	547
16	7.5	25.0	56.2	54.2	43.7	40.7	545
20	8.4	25.0	54.8	52.8	41.8	38.8	543
31.25	10.5	23.6	51.9	49.9	37.9	34.9	542
62.5	15	21.5	47.4	45.4	31.9	28.9	541
100	19.1	20.1	44.3	42.3	27.8	24.8	540
200	27.6	18.0	39.8	37.8	21.8	18.8	539
250	31.1	17.3	38.3	36.3	19.8	16.8	538
300	34.3	16.8	38.1	35.1	18.3	15.3	537
500	45.3	15.2	33.8	31.8	13.8	10.8	536

Color Code:

PAIR NO	COLOR
1	White and Blue
2	White and Orange
3	White and Green
4	White and Brown

Jacket Color (C1 C2):

 Grey (01)	 Blue (02)
 Red (03)	 White (04)
 Violet (05)	 Orange (06)
 Yellow (07)	 PE-Black (08)

Packaging: Available in Reel of 305m(1000ft) **(04)** / Reel of 500m(1640ft) **(05)**
(P1 P2) Length Tolerance: +/- 2 meter

Product Code / Part No:

Part No	Product Name	Euro Class	ETL Verified	UL Listed	UL Verified
32427-C1C2P1P2	Cat 6A F/FTP-LSZH	CPR-Eca	on demand	on demand	on demand
32428-C1C2P1P2	Cat 6A F/FTP-LSZH	CPR-Dca	on demand	on demand	on demand

Note: Higher CPR Category will be made available on demand

27/12/2023



The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, Sterlite Technologies makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. Sterlite Technologies obligations shall be only set forth in Sterlite Technologies standard terms and conditions of the sale and in no case, Sterlite Technologies be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product.
 Users of Sterlite Technologies products should make their own evaluation to determine the suitability of such each product for the specific application.