UL Product iQ®



Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at https://www.ul.com/about/locations.

Communications-, Audio/Video-, Data- and Other Signaling-circuit Accessories

COMPANY

STERLITE TECHNOLOGIES LTD

33/1/1 WAGDHARA RD U T OF DADRA & NAGERHAVELLI DADRA, Dadra and Nagar Haveli and Daman and Diu 396230 India

E325735

Flush mount plates, Model(s): NXFP01BSXX Where NX-STL FP-Face Plate XX-Colour

Flush mount plates, Model(s): NXFP01USXX Where NX-STL, FP-Face Plate, XX-Colour

Flush mount plates, Model(s): NXFP02BSXX Where NX-STL FP-Face Plate XX-Colour

Flush mount plates, Model(s): NXFP02USXX Where NX-STL, FP-Face Plate, XX-Colour

Keystone jacks, Model(s): NXIOC06SX090GY, NXIOC06SX180GY, NXIOC06UX090BK, NXIOC06UX180BK

Keystone jacks, Model(s): NXIOC6ASX090GY - (Punch down Keystone shielded Outlet 90° C6A), NX- STL. IO – Outlet. C6A- Cat6A. SX-shielded. 090-90 degree.

Keystone jacks, Model(s): NXIOC6ASX180GY - (Toolless Keystone shielded Outlet 180° C6A), NX- STL. IO – Outlet. C6A- Cat6A. SX-shielded. 180-180 degree.

Keystone jacks, Model(s): NXIOC6AUX090XX - (Punch Down Keystone Unshielded Outlet 90° C6A). NX- STL. IO – Outlet. C6A- Cat6A. UX-Unshielded. 090-90 degree. XX- colour

Keystone jacks, Model(s): NXIOC6AUX180XX - (Toolless Keystone Unshielded Outlet 180° C6A). NX- STL. IO – Outlet. C6A- Cat6A. UX- Unshielded. 180-180 degree.XX- colour

Modular patch cords, Model(s): NXPCC06SXZ26XXYY Where NX- STL, PC – Patch Cord, C06-Cat 6 SX- Shielded, UX- Unshielded, Z-LSZH, 26-26AWG, 24-24AWG, XX=Color, YY=Length in Meter.

Modular patch cords, Model(s): NXPCC06UXZ24XXYY Where NX- STL, PC – Patch Cord, C06-Cat 6 SX- Shielded, UX- Unshielded, Z-MA-USE-ZONNIE-STD MODELS: NXPCC06UXZ24XXYY Where NX- STL, PC – Patch Cord, C06-Cat 6 SX- Shielded, UX- Unshielded, Z-MA-USE-ZONNIE-STD MODELS: NXPCC06UXZ28XXYYLD - Where NX- STL, PC – Patch Cord, C06-Cat 6, UX- Unshielded, Z-LSZH, 28-28AWG, XX=Color, YY=Length in Meter, LD-LED

Modular patch cords, Model(s): NXPCC6AS5Z28XXYYLD - Where NXC6可以是S-S是性的整

ord, C**ƙéj6at 64**1, S

Shielept All-8266 Ries

Modular patch cords, Model(s): NXPCC6ASXZ26XXYY - where NX- STL, PC – Patch Cord, C6A-Cat 6A, SX- Shielded, Z-LSZH, 26-26AWG, XX=Color, YY=Length in Meter

Modular patch cords, Model(s): NXPCC6AUXZ24XXYY Where NX- STL, PC – Patch Cord, C6A-Cat 6A UX- Unshielded, Z-LSZH, 24-24AWG, XX=Color, YY=Length in Meter

Modular patch cords, Model(s): NXPCC6AUXZ28XXYY Where NX- STL PC – Patch Cord C6A-Cat 6A UX- Unshielded Z-LSZH 28-28AWG XX=Color YY=Length in Meter

Surface boxes, Model(s): NXSB01SM, NXSB02SM

Last Updated on 2024-06-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. <u>Learn more</u>