

estelan

Category 6 S/FTP Patch Cord



Cat6 S/FTP patch cord ensures secure Gigabit network connections by protecting against electromagnetic interference and noise. These are high-performance components available in a variety of lengths and colors, designed to meet or exceed CAT6 specifications. 26 AWG conductors are securely crimped with RJ45 plug to deliver superior performance.

Features & Benefits

- 26 AWG Stranded flexible cable
- High performance RJ-45 shielded Connectors with 50µm Gold Plated contacts
- Flexible Strain Relief Boot
- Soft latch-cover design for ease of handling
- Complies to ANSI/TIA-568 latest revision and other Equivalent standards

Regulatory Compliances/Certifications

- RoHS Directive (2011/65/EU+2015/863/EU)

Specifications

Mechanical Specifications	
Conductor AWG	26
Conductor Material	Stranded Bare Copper
Type of Cable	S/FTP
Number of Pairs	4
Application	Indoor
Insulation Diameter (mm)	1.03 (Nominal)
Insulation Material	PE
Jacket Type	LSZH
Cable Diameter (mm)	6.2 (Nominal)

Environmental Specifications	
Installation Temperature	0°C to 50°C
Storage Temperature	-20°C to +70°C
Operating Temperature	-10°C to +60°C

Part Number Configurator

Product Code	Product Type	Category	Shielding	Outer Sheath	Conductor Size	Colour	Length
ZX	PC	C06	SX	Z	26	GY	03

Part Code	Description
ZXPCC06SXZ26GY03	Category 6 26AWG S/FTP Patch Cord, LSZH, Grey, 3 Meters

Product Code

Product Type

Category

Shielding

Outer Sheath ¹

Conductor Size

Length

ZX

-

PC

Patch Cord

C06

CAT6

SX

S/FTP

Z

LSZH

26

26 AWG

Colour

BL

Blue

OR

Orange

GR

Green

GY

Grey

WH

White

RD

Red

BK

Black

YL

Yellow

X5

0.5 m

01

1 m

20

20 m

Note 1: Other options available on request

For additional information please contact your sales representative.

You can also visit our website at www.stl.tech

The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, STL makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. STL obligations shall be only set forth in STL standard terms and conditions of the sale and in no case, STL be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product. Users of STL products should make their own evaluation to determine the suitability of such each product for the specific application.