STC

estelan Modular Patch Panel



STL Modular Patch Panel offers fast and reliable installation of Unshielded/Shielded cables. A rear cable support bar is supplied which acts as a stress reliever for terminated cables. Each port of the panel is numbered for clear port identification. Patch Panel includes installation accessories.

Features & Benefits:

- Complies to ANSI/TIA-568.2-D, ISO/IEC 11801
- 19" RJ45 Snap in type Patch Panel
- Strain relief and cable management with inbuilt wire manager
- Covered under STL Warranty
- Panels provided with grounding wire

Regulatory Compliances:

• RoHS Directive (2011/65/EU+2015/863/EU)

Specifications

| General Specification | |
|-----------------------|--|
| Panel | Steel Plate Cold Commercial with Nickel Plating |
| Cabling Sequence | Т568 А & В |
| Panel Thickness | 1.5mm |
| Panel Color | Black (RAL 9005) |
| Port Identification | Yes |
| Outlet Type | CAT6 and CAT6A, available in Shielded and Unshielded option. |

| Environmental Specification | | |
|-----------------------------|----------------|--|
| Operating Temperature | -10°C to +60°C | |
| Storage Temperature | -20°C to +70°C | |
| Humidity | 10% - 90% RH | |

Ordering information:

| Part Code | Description |
|----------------|---|
| ZXPPUSSTRE1U24 | Patch Panel, Straight 1RU 24 Port Unloaded, UTP/STP with Cable Support |
| ZXPPUSSTRF1U24 | Patch Panel, Straight 1RU 24 Port Unloaded, UTP/STP w/o Cable Support bar |
| ZXCSSTR1U | Cable Support bar |

1/052025/IN

For additional information please contact your sales representative. You can also visit our website at <u>www.stl.tech</u>

The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, STL makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. STL obligations shall be only set forth in STL standard terms and conditions of the sale and in no case, STL be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product. Users of STL products should make their own evaluation to determine the suitability of such each product for the specific application.