


Making every conversation count

# **NEOX N62W Enterprise IP Phone**



The **NEOX N62W IP Phone** is designed for Business communication with advanced features. It includes a 2.8-inch main color display and a 2.4-inch secondary screen for added functionality.

This IP phone supports HD voice for clear sound quality and 12 SIP lines to manage multiple calls efficiently. It also offers gigabit Ethernet for fast connectivity and PoE (Power over Ethernet) for easy installation.

Additional features include a 6-way audio conferencing option, compatibility with EHS headsets, and support for BT and Wi-Fi dongles. These features ensure smooth and reliable communication for users.

# **Key Specifications**

**Display**: 2.8-inch main color screen and a 2.4-inch extended screen for DSS keys. **DSS and Line Keys**: 6 DSS keys, extendable to 30 via Pagination, 3 line keys for quick access

12 SIP Lines for efficient and Multi-Line Communication

Conference: 6-way audio conference for efficient collaboration.

**Connectivity**: Dual Gigabit ports with integrated PoE. **Headset Support**: compatible with EHS wireless headsets,

Wi-Fi dongles, and BT dongles.

**Adjustable Stand**: for 45° and 50° viewing angles. **Multiple Modes**: Handset, Hands-Free, and Headset

Flexible Installation: Desktop Stand or Wall Mount (optional)

**Optional External Power Supply** 

### **Network Features**

- IP Configuration: DHCP, Static IP, PPPoE
- IP Modes: IPv4, IPv6, Dual-Stack (IPv4 & IPv6)
- Dual 10/100/1000 Mbps Ethernet Ports with PC bypass support
- Network Access Control: 802.1X Authentication
- VPN Support: OpenVPN, L2TP
- VLAN Support for network segmentation
- QoS (Quality of Service) for optimized performance
- LLDP and CDP for network discovery and management
- Call Quality Monitoring: RTCP-XR (RFC3611) and VQ-RTCPXR (RFC6035)

### **Phone Features**

- Local Phonebook: Up to 1000 entries
- Remote Phonebook: XML/LDAP support (1000 entries)
- Call Logs: 1000 entries (Incoming, Outgoing, Missed)
- Blocked and Allowed Lists for call management
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft Keys for quick access
- Bluetooth Headset and Wi Fi Support via dongle
- Call Recording: Server-based support
- Screen Saver for display customization
- Network Time Synchronization
- Action URL/Active URI for automation
- uaCSTA for advanced call control



## **Provisioning and Control**

- Web Management Portal for easy configuration
- Configuration Management: Export/Import options
- Phonebook Management: Import/Export support
- Firmware Upgrade for seamless updates
- Web-Based Packet Dump for troubleshooting
- Syslog Support for system logging and diagnostics
- Auto-Provisioning: FTP, TFTP, HTTP, HTTPS, DHCP, OPT66, SIP PNP, TR-069

## **Calling Functions**

- · Make, Answer, or Reject Calls
- Hold and Resume Calls
- Mute/Unmute Microphone
- Call Waiting for incoming call alerts
- Redial Last Number
- **Speed Dial** for quick access to contacts
- Display or Hide Caller ID (Anonymous Call)
- Call Forwarding Options: Always, Busy, No Answer
- Call Transfer: Attended or Blind
- Call Pickup/Parking (Server-dependent)
- Auto-Answer for hands-free convenience
- Do Not Disturb (DND) mode for uninterrupted time
- 6-Way Audio Conferencing for group discussions
- Intercom Function for internal communication
- Hotline Setup for instant calling
- Hot Desking Support for shared workspace environments
- Voice Messaging (Stored on Server)

# Network Security and Protocols

 $\bullet$  SIP 2.0 over UDP, TCP, and TLS

Secure Media: SRTP, RTP/RTCP
VPN Support: OpenVPN, L2TP

• IP Configuration: DHCP, PPPoE

- IPv6 Compatibility for modern networks
- Network Discovery: LLDP (Link Layer Discovery Protocol)

• Authentication: 802.1X Network Access Control

• Encryption: AES-128 and AES-256 for data security

• Firewall Traversal: STUN

• Time Synchronization: SNTP

• File Transfer: FTP/TFTP

• Web Access: HTTP/HTTPS

• Remote Management: TR-069

### **Audio Features**

- Wideband ADC/DAC with 16KHz sampling for superior audio performance
- Full-Duplex Acoustic Echo Cancellation (AEC) for crystal-clear calls
- Wideband Audio Codecs: G.722, Opus
- Narrowband Audio Codecs: G.711a/u, G.723.1, G.726, G.729A/B, iLBC
- Advanced Voice Processing:
  - o Noise Reduction (NR)
  - o Automatic Gain Control (AGC)
  - o Voice Activity Detection (VAD)
  - o Comfort Noise Generation (CNG)
  - o Background Noise Estimation (BNE)
- Voice Quality Enhancements:
  - o Packet Loss Concealment (PLC)
  - o Dynamic Adaptive Jitter Buffer
  - o VQM (Voice Quality Monitoring)
- DTMF Support: In-band, Out-of-Band (RFC2833/SIP INFO)
- Handset with Hearing-Aid Compatibility (HAC)
- Handset with HD Voice Microphone & Speaker
   (Frequency Range: 0 ~ 7KHz, for Handset/Hands-free modes)



### **Device Specifications**

### **Display and Controls**

- Main LCD: 2.8-inch color screen (320x240 resolution)
- DSS Key-mapping LCD: 2.4-inch color screen (240x320 resolution)
- Keypad (41 keys):
  - o Standard Digits: 12 keys
  - o Line Keys: 3 (with LED indicator)
  - o DSS Keys: 6 (with LED indicator)
  - o Soft Keys: 4
  - o Function Keys: 6 (Hold, Call Forward, Conference, MWI, Headset, Redial)
  - o Navigation Keys: 4
  - o Volume Control: 3 keys (Up, Down, Mute Microphone)
  - o Page-Switch Key: 1 (with LED indicator)
  - o Hands-Free Key: 1 (with LED indicator)

#### **Connectivity and Ports**

- RJ9 Ports:
  - o Handset x1
  - o Headset x1

### • RJ45 Ports:

- o Network x1
- o PC x1 (Bridged to Network)
- USB2.0 Port: 1 (Standard A) for connecting USB BT dongle, USB Wi-Fi dongle, or flash drive
  - DC Power Input: DC 5V / 2A
  - DC Port: Φ5.5x2.1x10mm
  - Safety Keyhole: 1

#### Accessories and Installation

- HD Handset (RJ9) x1
- Standard RJ9 Handset Cord x1
- 1.5M CAT.5E Ethernet Cable x1
- Back Rack x1
- Status Indicator Light: Red
- Installation:
  - o Desktop Stand
  - o Wall-Mountable (Additional wall hanging parts required)

#### **Environmental Conditions**

• Operating Temperature: 0°C ~ 45°C

• Operating Humidity: 10% ~ 95%

### Why STL-Neox? -

Trusted Globally: CCaaS/UCaaS solution with 500+ customers worldwid

Certified Excellence: Make in India, Gartner-reviewed, ISO 27001/14001, CMMi Level 5, DOT-TRAI tested

All-in-One Platform: Unifies all communication needs on a single platform

Open SIP Protocol: Avoids vendor lock-in

**In-House Development & Customization:** Tailored to meet specific client needs **24x7 Professional Support:** Strong post-sales service for seamless operations

Value for Govt. Helplines, Telcos, Data Centers, and Enterprises Multi-Vendor Compatibility: Interoperable with various systems Compliance-Ready: Meets data privacy and security standards

### **About Sterlite Technologies Ltd. (STL)**

STL is a leading global optical and digital solutions company providing advanced offerings to build 5G, Rural, FTTx, Enterprise, and Data Centre networks. The company, driven by its purpose of 'Transforming Billions of Lives by Connecting the World', designs and manufactures in 4 continents with customers in more than 100 countries. Telecom operators, cloud companies, citizen networks, and large enterprises recognize and rely on STL for advanced capabilities in Optical Connectivity, Global Services, and Digital and Technology solutions to build ubiquitous and future-ready digital networks. STL's business goals are driven by customer-centricity, R&D and sustainability. Championing sustainable manufacturing, the company has committed to achieving Net Zero emissions by 2030.



Phone: +91 9712900567

